

**Listing of Claims:**

- 1    1. (Previously amended) A retroreflective article comprising:
  - 2                a) a microporous substrate containing a plurality of pores which are less than 0.5 µm in diameter; and
  - 4                b) a layer of reflective material, selected from the group consisting of metal coatings and dielectric coatings, wherein said layer of reflective material is in direct contact with the surface of the substrate such that said layer at least 6                partially obscures a plurality of the pores of the substrate.
- 1    2. (Previously amended) A retroreflective article, as set forth in claim 1, additionally 2                comprising a protective coating material layer, overlying said layer of reflective 3                material.
- 1    3. (Original) A retroreflective article, as set forth in claim 2, wherein said protective 2                coating material is selected from the group consisting of polyurethanes, 3                polymethylmethacrylate and copolymers thereof, styrene-acrylonitriles, 4                polystyrene, polycarbonate, organosiloxanes, amorphous polyolefins, evaporative 5                dielectric coatings and other transparent materials.
- 1    4. (Previously amended) A retroreflective article as set forth in claim 1, wherein said 2                substrate contains a plurality of pores which have diameters which are less than 3                450 nm.
- 1    5. (Original) A retroreflective article, as set forth in claim 1, wherein said substrate 2                is comprised of a nanoporous polymeric film.
- 1    6. (Previously amended) A retroreflective article, as set forth in claim 4, wherein said 2                substrate is a fabric.
- 1    7. (Previously amended) A retroreflective article, as set forth in claim 5, wherein said 2                substrate is selected from the group consisting of polyethylene, 3                polytetrafluoroethylene, polypropylene, polyethylene terephthalate,

4 polymethylmethacrylate and polyacetate.

1 8. (Previously amended) A retroreflective article, as set forth in claim 1, wherein said  
2 reflective material layer is a metal coating.

1 9. (Previously amended) A retroreflective article, as set forth in claim 8, wherein said  
2 reflective material is selected from the group consisting of aluminum, chromium,  
3 nickel, silver and gold.

1 10. (Original) A retroreflective article, as set forth in claim 9, wherein said reflective  
2 material is aluminum.

1 11. (Previously amended) A retroreflective article, as set forth in claim 10, wherein  
2 said reflective material layer has a thickness of between about 0.001 to about  
3 0.0001 inch.

1 12. (Original) A retroreflective article, as set forth in claim 1, wherein an optical  
2 performance enhancing characteristic has been introduced into said article.

1 13. (Original) A retroreflective article, as set forth in claim 12, wherein said optical  
2 performance enhancing characteristic is a repeating corner cube design.

1 14. (Previously amended) A retroreflective article, as set forth in claim 1, additionally  
2 comprising an adhesive layer located on a surface of said substrate opposite to the  
3 surface on which said reflective material layer is deposited.

1 15. (Original) A retroreflective article, as set forth in claim 1, affixed to a carrier  
2 substrate member via said adhesive layer.

1 16. (Currently amended) A method for the production of a reflective article comprising  
2 the steps of:

3 a) providing a substrate which contains pores which ~~has~~ have a diameter

4 of less than 0.5 microns; and

5               b) applying a layer of reflective material directly to the substrate in such  
6 a way that said layer at least partially obscures a plurality of the pores of the  
7 substrate, wherein said layer of reflective material is selected from a group  
8 consisting of metal coatings and dielectric coatings.

1 17. (Previously amended) The method, as set forth in claim 16, further comprising the  
2 step of applying a protective layer to said reflective article, overlying said layer of  
3 reflective material.

1 18. (Original) The method, as set forth in claim 17, wherein said protective coating  
2 material is selected from the group consisting of polyurethanes,  
3 polymethylmethacrylate and copolymers thereof, styrene-acrylonitriles,  
4 polystyrene, polycarbonate, organosiloxanes, amorphous polyolefins, evaporative  
5 dielectric coatings and other transparent materials.

1 19. (Currently Amended) The method, as set forth in claim 16, wherein said reflective  
2 material is a metal coating.

1 20. (Previously amended) The method, as set forth in claim 19, wherein said metal  
2 coating is selected from the group consisting of aluminum, chromium, nickel,  
3 silver and gold.

1 21. (Previously amended) The method, as set forth in claim 20, wherein said metal  
2 coating is aluminum and has a thickness of between 0.001 to about 0.0001 inch.

1 22. (Original) The method, as set forth in claim 16, further comprising the step of  
2 processing said article to introduce optical performance enhancing characteristics.

1 23. (Original) The method, as set forth in claim 22, wherein said step of processing to  
2 introduce optical performance enhancing characteristics comprises embossing said  
3 article using calendar rolls or flat plates.

1    24. (Original) The method, as set forth in claim 23, wherein said step of processing  
2       includes heating said calendar rolls.

1    25. (Original) The method, as set forth in claim 23, wherein said step of processing  
2       to introduce optical performance enhancing characteristics includes introducing  
3       a repeating corner cube design into said reflective layer.